

## LA-UR-19-26204

Approved for public release; distribution is unlimited.

Title: InSight, 3D modeling CTX impact

Author(s): Larmat, Carene  
Maguire, Ross  
Karakostas, Foivos  
Rolland, Lucie

Intended for: Insight Impact Working Group

Issued: 2019-07-01

---

**Disclaimer:**

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by Triad National Security, LLC for the National Nuclear Security Administration of U.S. Department of Energy under contract 89233218CNA000001. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.



InSight

JPL



CNES



DLR

LOCKHEED MARTIN

ETH

MPS

ISAE



Imperial College  
London




SEIS

to the heart of worlds

InSight

3D modeling CTX impact



Los Alamos  
NATIONAL LABORATORY  
EST. 1943


C. Larmat, R. Maguire, L. Rolland, F.  
Karakostas



- Introduction
- Model
  - Surface topography
  - Vertical model
- Results
  - Acoustic/elastic modeling with a resolution of 3s
  - Seismic only with a resolution of 0.5s (2Hz)




- Previous modelings:
  - Karakostas et al., 2018
  - Daubar et al., 2018
  - Garcia et al., 2017
- SPECFEM3D (Komatitsch et al., 1999, 2002): spectral element method, elastic, acoustic and poro-elastic modeling, gravity, GPU-accelerated, anisotropy.




**Amplitude at 5km of impact. Impact of meteorite of 2, 1 and 0.5m of diameter respectively.**

MOLA DEM 463m      HRSC DEM 100m (Golombek et al., 2016)






Model EH45Tcoldcrust1rq (Rivoldini et al. 2011).



- Regolith layer of 80m with the shallowest 20m with  $V_p=265\text{m/s}$  and  $V_s=150\text{m/s}$
- Subsequent layer of 1km with  $V_p = 2700\text{m/s}$  and  $V_s 1500\text{m/s}$
- Subsequent layer with a slow gradient.






Total elastic elements: 4.7M  
Total acoustic elements: 4.7M

Element size between 250m  
and 500m


Minimum period resolved 3s

432 processors; 4hrs to  
compute 140s of signal





**Vertical component modeled at Insight with a seismic source of Mw=-1.76. In black, the source was into the ground mimicking a perfect coupling into the ground, in blue the source was in the atmosphere, mimicking a “partial” coupling. On the left, waveform at the ground level. On the right, waveforms in the acoustic domain. Notice the difference of amplitude on the acoustic wave.**




Total elastic elements: 51M

Total acoustic elements: 0M

Element size between 25 and 500m (doubling): Minimum period resolved 0.5s

4608 processors; 16hrs to compute 140s of signal



- Working on benchmarking between SPECFEM3D and AXISEM.
- Need hypothesis, data on the thickness of the regolith layer.



- Working on benchmarking between SPECFEM3D and AXISEM.
- Need hypothesis, data on the thickness of the regolith layer.
- Need to develop a 3D model of scattering.